






- Ready for surface mounting out of the box
- 2850-3300lm
- 120° beam angle
- 3000K/4000K/5700K 3-CCT selectable
- L70 lifetime >53000hrs
- Indoor use only



← 900mm →



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Order Code 66665

General Data

Lamp base	N/A
Design	N/A

Geometric Data

Length (mm)	900mm
Width x Height (mm)	80x 34mm
Weight (g)	860g


Electric Data

Wattage	30W
Voltage	200-240Vac
Power Factor	0.9
Operating Frequency	50/60Hz

Photometric Data

Total Luminous Flux (lm)	2850-3300lm
CRI	>80
CCT	3000K/4000K/5700K – 3-CCT
Luminous Intensity (cd)	N/A
Beam Angle (°)	120°
Lifetime(L70)	>53000 hrs
Operating Temperature	-20 ~ 45°C





Order Code	66665
-------------------	-------

Product Description	LED Indoor Integrated Batten 30W 900mm 3CCT 2850-3300lm
----------------------------	---

Technical Packaging Details

Giftbox Barcode	4895117966655
Inner Carton Barcode	N/A
Outer Carton Barcode	24895117966659
Pack Dimensions (LxWxH)	910X88X42mm
Pack Weight	TBC
Carton Qty (Shipping Unit)	10
Carton Dimensions (LxWxH)	940x210x250mm
Cartons/Layer	5
Layers/Pallet	4
Units/Pallet	200