






- Ready for surface mounting out of the box
- 3200-3900lm
- 120° beam angle
- 3000K/4000K/5700K 3-CCT selectable
- L70 lifetime >53000hrs
- Indoor use only



1200mm



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Order Code 66666

General Data

Lamp base	N/A
Design	N/A

Geometric Data

Length (mm)	1200mm
Width x Height (mm)	80x 34mm
Weight (g)	1120g

Electric Data

Wattage	35W
Voltage	200-240Vac
Power Factor	0.9
Operating Frequency	50/60Hz

Photometric Data

Total Luminous Flux (lm)	3200-3900lm
CRI	>80
CCT	3000K/4000K/5700K – 3-CCT
Luminous Intensity (cd)	N/A
Beam Angle (°)	120°
Lifetime(L70)	>53000 hrs
Operating Temperature	-20 ~ 45°C





Order Code	66666
-------------------	-------

Product Description	LED Indoor Integrated Batten 35W 1200mm 3CCT 3200-3900lm
----------------------------	--

Technical Packaging Details

Giftbox Barcode	4895117966662
Inner Carton Barcode	N/A
Outer Carton Barcode	24895117966666
Pack Dimensions (LxWxH)	1210X88X42mm
Pack Weight	TBC
Carton Qty (Shipping Unit)	10
Carton Dimensions (LxWxH)	1240x210x250mm
Cartons/Layer	5
Layers/Pallet	4
Units/Pallet	200